

This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	T.Shihua	1/8/14	1/8/14

1 Electrical

- 1.1 Impedance: 50Ω
1.2 Frequency: DC-50GHz
1.3 VSWR: 1.25:1

2 Mechanical&Environmental


- 2.1 Temperature range -55°C ~+165°C
2.2 Durability(matings) >500
2.3 RoHs Compliant Yes

3 Material&Finish

- 3.1 Pin contact: Beryllium-Copper, gold plated
3.2 Body: Stainless Steel(SUS303), Passivated
3.3 Insulators: PEI

4 Interface Standards

- 4.1 2.4 IEEE STD 287-2007



Notes:

- 1.ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2.CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T.Shihua 1/8/14		TITLE:	
ENGINEER: C.Too 1/8/14		Precision Adapter 2.4 Male to 2.4 Male	
APPROVED: W.Qiang 1/8/14			
TOLERANCES UNLESS OTHERWISE SPECIFIED			
X ±0.50		 DIMENSION IN MILLIMETERS (mm)	
X ±0.20			
XX ±0.10			
ANGLES ±1°			
PART NO: 2.4-JJG		SIZE: A4	
		SCALE: N/A	
		SHEET: 1/1	
		REV: A	