
This document contains proprietary information and such informationmay not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	———	T.Shihua	07/04/16	07/04/16



1 Electrical

1.1 Impedence	50Ω
1.2 Frequency	0～6GHz
1.3 VSWR	1.30:1

2 Environmental&Mechanical

2.1 Temperature range	-45℃～125℃
2.2 RoHs Compliant	
2.3 Durability	>500 cycles

3 Materials&plating

3.1 Body:	Brass, nickel plated
3.2 Insulator:	Teflon
3,3 Contact Pin:	Bronze, Gold plated
3.4 O-Ring:	Silicon Rubber

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T.Shihua 07/04/16	TITLE: RF Coaxial Connector N female Conn. For RG58 Cable				
ENGINEER: C.Tao 07/04/16					
APPROVED: W.Qiang 07/04/16					
TOLERANCES UNLESS OTHERWISE SPEFICIED X ±0.50 .X ±0.20 .XX ±0.10 ANGLES ±1°		www.rf-connector-china.com			
		DIMENSION IN MILLIMETERS (mm)			
	PART NO: N-K5A	SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A