

1		2		3		4	
This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission							
REV		DESCRIPTION OF REVISION		ECN NO.		BY	
A		Initial Release				T. Shihua	
DATE		13/05/15		13/05/15		APPROVED	
13/05/15						13/05/15	

1 Electrical

1.1 Impedence

1.2 Frequency

1.3 Dielectric withstanding voltage

1.4 Insulation resistance

1.5 VSWR

2 Environmental&Mechanical

2.1 Temperature range

2.2 RoHs Compliant

2.3 Durability

3 Materials&plating

3.1 Body:

3.2 Insulator:

3.3 Contact Pin:

3.4 Coupling nut:

50 Ω

DC~6GHz

1500V(volts RMS)

≥5000M Ω

≤1.30

-40℃~125℃

>500 cycles

Brass, Nickel plated

Teflon

Brass, Gold plated

Brass, Nickel plated

40.3

16.0

www.terulai.com

RF Coaxial Connector

N male Conn. For LMR400/RG213

Cable Clamp

Part No: N-J400A

Size: A4

Scale: N/A

Sheet: 1/1

Rev: A

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME

2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY