



This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission



Recommended Mounting Hole



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

REV	DESCRIPTION OF REVISION	TRL NO.	BY	DATE	APPROVED
A	Initial Release		T.Shihua	04/03/2022	04/03/2022

1. Electrical Performance
 - 1.1 Impedance characteristic: 50 Ω
 - 1.2 Frequency range: DC~11GHz
 - 1.3 VSWR voltage ratio: ≤1.20@6GHz
 - 1.4 Insertion Loss (dB): ≤0.05xSqt. (f_GHz)
 - 1.5 Insulation resistance: ≥5000MΩ
 - 1.6 Dielectric withstanding voltage: 1000V
2. Environmental & Mechanical Performance
 - 2.1 Temperature range: -55℃~+125℃
 - 2.2 RoHs Compliant
 - 2.3 Durability: >500 cycles (次)

3. Materials & Finish
 - 3.1 Body: Brass, Nickel Plated, Yellow, Gold
 - 3.2 Insulator: Teflon, PTFE, PEEK
 - 3.3 Contact Pin: Gold Plated, Silver Plated, Copper, Gold
 - 3.4 O-ring: Silicone Rubber, NBR

DRAWN: L.hao 26/10/2024		TITLE		www.rf-connector-china.com	
ENGINEER: T.shan 26/10/2024		RF Coaxial Adaptor		DIMENSION IN MILLIMETERS (mm)	
APPROVED: T.haijun 26/10/2024		N Female to SMA Female Bulkhead		SCALE: 1:1	
TOLERANCES UNLESS OTHERWISE SPECIFIED		PART NO: N/SMA-KYKC		SHEET: 1/1	
X ±0.50				REV: YA	
.X ±0.20					
.XX ±0.10					
ANGLES ±1°					