

This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	TRL NO.	BY	DATE	APPROVED
A	Initial Release	—	T. Shihua	08/09/2022	08/09/2022

1 Electrical


- 1.1 Impedance: $50\ \Omega$
- 1.2 Frequency: DC~40.0GHz
- 1.3 VSWR: ≤ 1.40
- 1.4 Insulation resistance: $\geq 5000M\ \Omega$
- 1.5 Dielectric strength: 500V
- 1.6 Center contact $\leq 6.0m\ \Omega$
- 1.7 Outer contact $\leq 2.0m\ \Omega$

2 Environmental&Mechanical


- 2.1 Temperature range: $-55^{\circ}\text{C}\sim+125^{\circ}\text{C}$
- 2.2 RoHs Compliant
- 2.3 Durability: >500 cycles

3 Materials&Finish

- 3.1 Body: Brass, Gold plated
- 3.2 Insulator: Teflon
- 3.3 Contact Pin: Bronze, Gold plated




Recommended cable stripping dimensions



Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T. Shihua 08/09/2022	TITLE RF Coaxial Connector SMP Male Limited Detent For .086 cable	 www.rf-connector-china.com			
ENGINEER: C. Tao 08/09/2022					
APPROVED: W. Qiang 08/09/2022		 DIMENSION IN MILLIMETERS (mm)			
TOLERANCES UNLESS OTHERWISE SPECIFIED X ± 0.50 .X ± 0.20 .XX ± 0.10 ANGLES $\pm 1^{\circ}$	PART NO: SMP-JB2-F	SIZE: A4	SCALE: 8:1	SHEET: 1/1	REV: VA