

This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release		T.Shihua	18/7/13	18/7/13

1 Electrical



1.1 Impedance	50 Ω
1.2 Frequency	0~11GHz
1.3 Dielectric withstanding voltage	1500V(volts RMS)
1.4 Center contact resistance	$\leq 1\text{M}\Omega$
1.5 Outer contact resistance	$\leq 0.2\text{M}\Omega$
1.6 Insulation resistance:	$\geq 5000\text{M}\Omega$

2 Environmental&Mechanical

2.1 Temperature range	-55℃~155℃
2.2 RoHs Compliant	
2.3 Durability	>500 cycles

3 Materials&plating

3.1 Body:	Brass, nickel plated
3.2 Insulator:	Teflon
3.3 Contact Pin:	Bronze, Gold plated



Notes:

- 1.ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2.CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T.Shihua 18/07/13	TITLE: N-KYD N female B/H Conn. For Terminal	 www.teruilai.com			
ENGINEER: C.Tao 18/07/13					
APPROVED: W.Qiang 18/07/13		 DIMENSION IN MILLIMETERS (mm)			
TOLERANCES UNLESS OTHERWISE SPECIFIED .X ± 0.50 .XX ± 0.20 .XXX ± 0.10 ANGLES $\pm 1^\circ$	PART NO: TRL-NF-282866	SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A