

1		2		3		4	
This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission							
1 Electrical 1.1 Impedance 50 Ω 1.2 Frequency DC~4GHz 1.3 VSWR <1.25:1		2 Environmental & Mechanical 2.1 Temperature range -45℃~+125℃ 2.2 RoHS Compliant 2.3 Durability >500 cycles		3 Material & Plating 3.1 Body: Stainless Steel, Passivated 3.2 Insulator: Teflon 3.3 Contact Pin: Brass, gold plated 3.4 Nut: Brass, gold plated 3.5 Gasket: Silicon Rubber		4	
A							
B							
B							

Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T. Shihua 18/08/13		TITLE:		RF Coaxial Connector		www.rf-connector-china.com	
ENGINEER: C. Tao 18/08/13				BNC Male Conn. for TLA360/CXN3507 Cable With Armor		DIMENSION IN MILLIMETERS (mm)	
APPROVED: H. Qiang 18/08/13				TOLERANCES UNLESS OTHERWISE SPECIFIED		D	
				X ±0.50		1/1	
				.X ±0.20		A4	
				.XX ±0.10		SHEET:	
				ANGLES ±1°		REV:	
						A	
PART NO: BNC-J3507G-KJ		3		4			