

This document contains proprietary information and such information may not be disclosed to others for any purposes, not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	T.Shihua	16/6/15	16/6/15

1 Electrical data

- 1.1 Impedance: 50Ω
- 1.2 Frequency: DC-27GHz
- 1.3 VSWR 1.15:1@18G; 1.25:1 @27G

2 Mechanical data


- 2.1 Temperature range -55°C ~+165°C
- 2.2 Durability(matings) >500

3 Material&Finish

- 3.1 Pin contact: Beryllium-copper, gold plated
- 3.2 Body: Stainless Steel(SUS303), Passivated
- 3.3 Insulators: PTFE

4 Interface Standards

- 4.1 SMA MIL-STD-348A



Notes:

- 1.ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2.CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: T.Shihua 16/6/15	TITLE:		Xi'an Reach-Line Technology Co., Ltd				
ENGINEER: C.Too 16/6/15	SMA-KYKG						
APPROVED: W.Qiang 16/6/15	SMA Female to Female Bulkhead Adaptor						
TOLERANCES UNLESS OTHERWISE SPECIFIED				DIMENSION IN MILLIMETERS (mm)			
X ±0.20				SIZE:	SCALE:	SHEET:	REV:
XX ±0.20				A4	N/A	1/1	A
ANGLES 3°							
PART NO: TRL-ZJQ-308910							